

CKS PAINT

Alkali-Resistant Sealing Primer (Sanded, Tintable)

(Interior Walls)



Product Description

This is a premium all-purpose water-based primer containing glass beads, and it is tint-compatible. It delivers excellent sealing capacity, effectively blocking the leaching of alkaline substances from wall substrates and preventing water vapor penetration. Boasting strong adhesion, mildew resistance and alkali resistance, it provides in-depth protection for wall surfaces. This avoids common wall defects including paint peeling, mold growth, mottling and yellowing. Meanwhile, it enhances the fullness of topcoat films, reduces topcoat consumption, and maintains an elegant and premium decorative finish for a long time.

Packaging

25kg/pail

Scope of Application

Suitable for use on interior walls in buildings.

Product Features

- Alkali-Sealing
- Good coverage
- Enhanced Adhesion

Theoretical Coverage

3.5 ~ 4 m²/kg

Application Notes

1. Recommended to use with little or no water dilution.
2. Apply by roller for 1 coat.
3. All diluted coating shall be used up in one session.
4. Seal residual coating tightly during work breaks or after construction to prevent drying. Clean tools and contaminated garments immediately; dried coating is hard to remove.
5. Do not construct when ambient temperature is below 8°C and relative humidity exceeds 70% RH, as film formation will be impaired.

Transportation and Storage

- Transportation: This coating is non-flammable, non-explosive, safe, non-toxic, and harmless. Avoid excessive stacking.
- Storage: Store in a sealed container in a dry, cool place at a temperature of 5–30° C. Avoid frost and direct sunlight.
- Shelf life: Minimum 18 months under proper conditions.