

CKS PAINT

ALKALI-RESISTANT SEALING PRIMER

(Exterior Walls)



Product Description

Alkali-Resistant Sealing Primer is a high-performance all-purpose water-based primer. It delivers excellent sealing capacity, effectively blocking the leaching of alkaline substances from wall substrates and preventing water vapor penetration. Boasting strong adhesion, mildew resistance and alkali resistance, it provides in-depth protection for wall surfaces. This avoids common wall defects including paint peeling, mold growth, mottling and yellowing. Meanwhile, it enhances the fullness of topcoat films, reduces topcoat consumption, and maintains an elegant and premium decorative finish for a long time.

Packaging

20kg/pail

Scope of Application

Suitable for use on building exterior walls..

Product Features

- Alkali-Sealing
- Mould & Moisture Protection
- Enhanced Adhesion

Theoretical Coverage

7 ~ 9 m²/kg

Application Notes

1. Primer may be diluted with clean water at 15%–20%.
2. Apply by roller or spray gun for 1 coat.
3. All diluted coating shall be used up in one session.
4. Seal residual coating tightly during work breaks or after construction to prevent drying. Clean tools and contaminated garments immediately; dried coating is hard to remove.
5. Construction is strictly prohibited when environmental temperatures are below 8° C, relative humidity is above 70% RH, or during rainy, foggy, or windy weather, as these conditions may affect the coating's formation.

Transportation and Storage

- Transportation: This coating is non-flammable, non-explosive, safe, non-toxic, and harmless. Avoid excessive stacking.
- Storage: Store in a sealed container in a dry, cool place at a temperature of 5–30° C. Avoid frost and direct sunlight.
- Shelf life: Minimum 18 months under proper conditions.