

CKS PAINT

Protective Top Coat (Exterior Walls)



Product Description

Protective Top Coat, specially formulated to provide long-lasting protection for exterior wall finishes. Weather-resistant, stain-resistant, acid- and alkali-resistant, and UV-resistant. The paint film features a translucent matte finish that remains clear without fogging, preserving the original texture and color of the base coat. Breathable and waterproof, with excellent adhesion, it resists mold and moisture, significantly enhancing wall durability and effortlessly achieving a long-lasting, attractive, high-quality exterior wall finish.

Packaging

20kg/pail

Scope of Application

Suitable for use on building exterior walls.

Product Features

- Stain-Resistant & Easy to Clean
- Crystal Clear & Beautiful Finish
- Resists UV yellowing

Theoretical Coverage

5.5–6.5 m²/kg

Application Notes

1. The Protective Top Coat may be diluted with clean water at 15%–20%.
2. Apply by roller or spray gun for 1 coat.
3. All diluted coating shall be used up in one session.
4. Seal residual coating tightly during work breaks or after construction to prevent drying. Clean tools and contaminated garments immediately; dried coating is hard to remove.
5. Construction is strictly prohibited when environmental temperatures are below 8° C, relative humidity is above 70% RH, or during rainy, foggy, or windy weather, as these conditions may affect the coating's formation.

Transportation and Storage

- Transportation: This coating is non-flammable, non-explosive, safe, non-toxic, and harmless. Avoid excessive stacking.
- Storage: Store in a sealed container in a dry, cool place at a temperature of 5–30° C. Avoid frost and direct sunlight.
- Shelf life: Minimum 18 months under proper conditions.