

CKS PAINT

Protective Top Coat (Interior Walls)



Product Description

Protective Top Coat delivers long-term protection for interior wall finishes. It boasts superior scrub resistance and stain resistance, and retards light-triggered yellowing. It effectively prevents cooking fumes, fingerprints and water stains from penetrating wall surfaces. The matte clear film stays transparent without clouding, preserving the original texture and colour of the base coat. Breathable and water-resistant with excellent adhesion, it resists mould and dampness, greatly enhancing wall durability, and creating elegant interior wall finishes that remain beautiful and easy to clean over time.

Packaging

20kg/pail

Scope of Application

Suitable for use on interior walls in buildings.

Product Features

- Stain-Resistant & Easy to Clean
- Crystal Clear & Beautiful Finish
- Resists light-induced yellowing

Theoretical Coverage

5.5–6.5 m²/kg

Application Notes

1. The Protective Top Coat may be diluted with clean water at 15%–20%.
2. Apply by roller for 1 coat.
3. All diluted coating shall be used up in one session.
4. Seal residual coating tightly during work breaks or after construction to prevent drying. Clean tools and contaminated garments immediately; dried coating is hard to remove.
5. Do not construct when ambient temperature is below 8°C and relative humidity exceeds 70% RH, as film formation will be impaired.

Transportation and Storage

- Transportation: This coating is non-flammable, non-explosive, safe, non-toxic, and harmless. Avoid excessive stacking.
- Storage: Store in a sealed container in a dry, cool place at a temperature of 5–30° C. Avoid frost and direct sunlight.
- Shelf life: Minimum 18 months under proper conditions.